



## ABOUT AZEK

AZEK® is the leading brand of cellular pvc offering the unequalled combination of Uniformity, Durability, Workability, and Beauty.

Using a state-of-the-art manufacturing process, AZEK is manufactured in standard trim dimensions such as trimboards, sheets, cornerboard, and beadboard. A perfect wood replacement product for non-structural applications, AZEK performs beautifully in standard or custom trim applications.

Available at professional lumberyards across the nation and Canada, AZEK trim products have changed the way the industry thinks about trim. Once you look, it's all you'll see.

## PRODUCT INFO

**UNIFORMITY.** Manufactured in a proprietary process, AZEK Trimboards are consistent and uniform throughout with no voids. Available in premium lengths (18 or 20 foot), all edges are square and smooth so joints and corners match easily. And protective packaging applied at the manufacturer helps to insure that AZEK bundles arrive in good condition.

**DURABILITY.** AZEK trim products will not split, cup, rot, warp or twist. In fact, since AZEK can be used in direct contact with the ground or masonry it is the perfect choice for moisture-prone applications like garage door jambs and hot tub surrounds. And AZEK trim products have a 25-year warranty.

**WORKABILITY.** Cut, rout or mill AZEK trim products to fit your unique design needs using traditional woodworking tools. AZEK can be nailed, glued, or screwed and is easily bent or shaped into curved applications. Without a grain, AZEK can be fastened close to the edge without splitting. And since the entire length of each piece is usable there's less wasted material. For more information, see the [Installation Guidelines](#).

**BEAUTY.** AZEK Trimboards complement all housing exteriors from traditional brick or cedar shake to fiber cement and other sidings. Manufactured in natural, semi-matte white, AZEK performs beautifully as trim, fascia, soffit, corner board, ceilings, decorative millwork, custom molding, wainscoting, and more. While AZEK can be painted or stained for a custom color; painting is never required for protection.

Once you look, it's all you'll see.

PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND SUBJECT TO STOCK BEING ON HAND



3001 Southwest Blvd. • Kansas City, MO 64108-3616  
816-753-6262 • 800-456-2148 • Fax 816-753-7935  
[www.SchutteLumber.com](http://www.SchutteLumber.com)

# AZEK Product Line

## **Trimboards - Frontier Series**

| Nominal Dimensions | Actual Dimensions    | Pcs/Unit | Unit Weight |
|--------------------|----------------------|----------|-------------|
| 1x4-18'            | 3/4" x 3-1/2" - 18'  | 221      | 2991        |
| 1x6-18'            | 3/4" x 5-1/2" - 18'  | 136      | 2901        |
| 1x8-18'            | 3/4" x 7-1/4" - 18'  | 102      | 2872        |
| 1x10-18'           | 3/4" x 9-1/4" - 18'  | 85       | 3036        |
| 1x12-18'           | 3/4" x 11-1/4" - 18' | 68       | 2961        |
| 1x16-18'           | 3/4" x 15-1/4" - 18' | 51       | 2879        |
| 5/4x4-18'          | 1" x 3-1/2" - 18'    | 156      | 2833        |
| 5/4x6-18'          | 1" x 5-1/2" - 18'    | 96       | 2747        |
| 5/4x8-18'          | 1" x 7-1/4" - 18'    | 72       | 2718        |
| 5/4x10-18'         | 1" x 9-1/4" - 18'    | 60       | 2873        |
| 5/4x12-18'         | 1" x 11-1/4" - 18'   | 48       | 2803        |
| 5/4x16-18'         | 1" x 15-1/4" - 18'   | 36       | 2803        |

## **Beadboard**

|                 |                      |     |      |
|-----------------|----------------------|-----|------|
| 1/2" x 6" - 18' | 1/2" x 5-1/2" - 18'  | 200 | 2775 |
| 5/8" x 4" - 18' | 5/8" x 3-5/16" - 18' | 260 | 2775 |

## **Cornerboard - Frontier & Traditional Series**

|                     |                           |    |      |
|---------------------|---------------------------|----|------|
| 5/4 x 4" x 4" - 10' | 1 x 3-1/2" x 3-1/2" - 20' | 72 | 1290 |
| 5/4 x 4" x 4" - 20' | 1 x 3-1/2" x 3-1/2" - 20' | 72 | 2580 |
| 5/4 x 6" x 6" - 10' | 1 x 5-1/2" x 5-1/2" - 10' | 48 | 1422 |
| 5/4 x 6" x 6" - 20' | 1 x 5-1/2" x 5-1/2" - 20' | 48 | 2844 |

## **Millwork**

|             |                       |
|-------------|-----------------------|
| Brick Mould | 1-1/8" x 2" - 17'     |
| Crown Mould | 11/16" x 3-5/8" - 16' |
| Drip Cap    | 11/16" x 1-5/8" - 16' |

## **Adhesive**

|                  |
|------------------|
| 4 oz. container  |
| 8 oz. container  |
| 16 oz. container |

## **Sheets - Traditional Smooth**

|                 |      |    |      |
|-----------------|------|----|------|
| 4' x 8' - 3/8"  | same | 30 | 1260 |
| 4' x 10' - 3/8" | same | 30 | 1610 |
| 4' x 8' - 1/2"  | same | 25 | 1250 |
| 4' x 10' - 1/2" | same | 25 | 1575 |
| 4' x 8' - 5/8"  | same | 25 | 1573 |
| 4' x 10' - 5/8" | same | 25 | 1952 |
| 4' x 8' - 3/4"  | same | 20 | 1610 |
| 4' x 10' - 3/4" | same | 20 | 2000 |
| 4' x 12' - 3/4" | same | 20 | 2400 |
| 4' x 8' - 1"    | same | 20 | 2150 |
| 4' x 10' - 1"   | same | 20 | 2675 |

PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND SUBJECT TO STOCK BEING ON HAND



3001 Southwest Blvd. • Kansas City, MO 64108-3616  
 816-753-6262 • 800-456-2148 • Fax 816-753-7935  
[www.SchutteLumber.com](http://www.SchutteLumber.com)

**AZEK® trim products are the #1 brand of trim. AZEK products are the perfect replacement for wood in all non-stress and non-load bearing applications.**

## STORAGE AND HANDLING

- Store AZEK trim products on a flat and level surface.
- Since AZEK trim products are more flexible than wood, they may conform to uneven surfaces.
- AZEK trim products have a density comparable to pine and should be handled in a fashion as pine would be handled to avoid damage.
- Units of AZEK are shipped from the manufacturer in a protective covering. If covering has been removed, take care to keep product free of dirt and debris at jobsite. If product gets dirty, clean after installation.

## CUTTING

- AZEK products can be cut using the same tools used to cut lumber.
- Carbide tipped blades designed to cut wood work well. Avoid using fine tooth metal cutting blades.
- Rough edges from cutting may be caused by excessive friction, poor board support, or worn or improper tooling.

## DRILLING

- AZEK products can be drilled using the same tools used to drill lumber.
- Drilling AZEK products is similar to drilling a hardwood. Care should be taken to avoid frictional heat build-up.
- Use standard woodworking drills. Do not use drills made for normal rigid PVC.
- Periodic removal of AZEK shavings from the drill hole may be necessary.

## ROUTING

- AZEK products can be routed using standard router bits and the same tools used to rout lumber.
- Carbide tipped router bits are recommended.
- Routing AZEK products provides a crisp, clean edge.

## FASTENING

- For best results, use fasteners designed for wood trim and wood siding (thinner shank, blunt point, full round head).
- To take advantage of the performance of AZEK, use a highly durable fastener such as stainless steel or hot dipped galvanized.
- Staples, small brads, and wire nails must not be used.
- The fasteners should be long enough to penetrate the solid wood substrate a minimum of 1 1/2".
- Standard nail guns work well with AZEK trim products.
- Like wood, use 2 fasteners per every framing member for trimboard applications. Trimboards 12" or wider, as well as sheets, will require additional fasteners. See Figure 1 below.
- Fasteners must be installed no more than 2" from the end of each board. See Figure 2 below.
- AZEK should be fastened into a flat, solid substrate. Fastening AZEK into hollow or uneven areas must be avoided.
- Pre-drilling is typically not required unless a large fastener is used or product is installed in low temperatures.
- 3/8" and 1/2" sheet product is not intended to be ripped into trim pieces. These profiles must be glued to a substrate and mechanically fastened.




Figure 1

For Trimboards 12" or wider and sheets, use more than 2 fasteners per framing member.



Figure 2

Fasteners no more than 2" from end of board.

## PAINTING

- AZEK products do not require paint for protection, but may be painted to achieve a custom color.
- Use a 100% acrylic latex paint with a Light Reflective Value (LRV) of 55 or higher.
- For paint colors equivalent to an LRV of 54 or lower, paints specifically designed for such applications must be used, such as Sherwin-Williams VinylSafe™ coatings.
- Follow the paint manufacturer's recommendations to apply.
- No special surface preparations are required prior to painting - just ensure the AZEK surfaces are clean and dry.
- Moisture cycling is a main reason for paint failure on wood. Since AZEK absorbs no moisture paints last longer on AZEK than wood.

## GLUING

- For best results, glue all AZEK to AZEK joints such as window surrounds, long fascia runs, etc., with AZEK Adhesive to prevent joint separation.
- The glue joint should be secured with a fastener and/or fastened on each side of the joint to allow adequate bonding time.



- AZEK Adhesive has a working time of 10 minutes and will be fully cured in 24 hours.
- If standard pvc cements are used, keep in mind these products typically cure quickly which will result in limited working time and may reduce adhesive strength.
- For best results, surfaces to be glued should be smooth, clean and in complete contact with each other.
- To bond AZEK to other substrates, various adhesives may be used. Consult adhesive manufacturer to determine suitability.

## EXPANSION & CONTRACTION

- AZEK products expand and contract with changes in temperature.
- Properly fastening AZEK material along its entire length will minimize expansion and contraction.
- When properly fastened, allow 1/8" per 18 foot of AZEK product for expansion and contraction. Joints between pieces of AZEK should be glued to eliminate joint separation. See "Gluing" section above.
- When gaps are glued on a long run of AZEK, allow expansion and contraction space at ends of the run.

## SPANNING

- AZEK products must not be used in load bearing applications, but may be used in spanned applications such as soffits and ceilings.
- For soffit installations:
  - For spans of 16" - 24", use a 1x AZEK product.
  - When using AZEK Beadboard, fasten every 12" or less.
  - Install AZEK Beadboard perpendicular to structure.
- For ceiling installations:
  - For spans of 16" - 24", use a 1x AZEK product.
  - When using AZEK Beadboard or thinner AZEK product, fasten every 16" or less.
  - If temperature at time of installation is 40° F or below, spans need to be decreased to 12".
- Never span AZEK products more than 24".

FOR ADDITIONAL INFORMATION:  
VISIT [WWW.AZEK.COM](http://WWW.AZEK.COM) OR CALL (877)-ASK-AZEK.